


# Bendy Packers




TAPASAN Bendy Packers are products that allow point repair of bends in pipes. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. The biggest advantage is that it allows repairs to be made in these areas by turning from 30°, 45° and 90° bends.

\*Can be produced as a Push Rod compatible head.


Product Code : DP




Connection Type




Back Hook Design



Patch Length Stripes



Push Rod Connection



Push Rod Connection

Product Code	Size Usage Range		Max. Working Pressure (bar) / (psi)	Deflated Plug Dimensions			Approx. Weight (kg) / (lbs)
	Min. Diameter (mm) / (inch)	Max. Diameter (mm) / (inch)		Diameter (mm) / (inch)	Lenght (mm) / (inch)	Total Lenght (mm) / (inch)	
	DP10012	100 / 4"		2.0 / 29	43 / 1.7"	1200 / 47.2"	
DP10015	100 / 4"		2.0 / 29	43 / 1.7"	1500 / 59.0"	1850 / 72.8"	1.7 / 3.7
DP10020	100 / 4"		2.0 / 29	43 / 1.7"	2000 / 78.7"	2350 / 92.5"	2.2 / 4.8
DP10030	100 / 4"		2.0 / 29	43 / 1.7"	3000 / 118.1"	3350 / 131.8"	3.4 / 7.4
DP10040	100 / 4"		2.0 / 29	43 / 1.7"	4000 / 157.4"	4350 / 171.2"	4.5 / 9.9
DP10050	100 / 4"		2.0 / 29	43 / 1.7"	5000 / 196.8"	5350 / 210.6"	5.6 / 12.3
DP10012512	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	1200 / 47.2"	1550 / 61.0"	1.9 / 4.1
DP10012515	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	1500 / 59.0"	1850 / 72.8"	2.2 / 4.8
DP10012520	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	2000 / 78.7"	2350 / 92.5"	2.9 / 6.3
DP10012530	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	3000 / 118.1"	3350 / 131.8"	4.4 / 9.6
DP10012540	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	4000 / 157.4"	4350 / 171.2"	5.8 / 12.7
DP10012550	100 / 4"	125 / 5"	2.0 / 29	64 / 2.5"	5000 / 196.8"	5350 / 210.6"	7.3 / 16.4
DP15012	150 / 6"		2.0 / 29	71 / 2.8"	1200 / 47.2"	1550 / 61.0"	2.3 / 5.0
DP15015	150 / 6"		2.0 / 29	71 / 2.8"	1500 / 59.0"	1850 / 72.8"	2.9 / 6.3
DP15020	150 / 6"		2.0 / 29	71 / 2.8"	2000 / 78.7"	2350 / 92.5"	3.8 / 8.3
DP15030	150 / 6"		2.0 / 29	71 / 2.8"	3000 / 118.1"	3350 / 131.8"	5.8 / 12.7
DP15040	150 / 6"		2.0 / 29	71 / 2.8"	4000 / 157.4"	4350 / 171.2"	7.7 / 16.9
DP15050	150 / 6"		2.0 / 29	71 / 2.8"	5000 / 196.8"	5350 / 210.6"	9.7 / 21.3
DP15017012	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	1200 / 47.2"	1550 / 61.0"	3.2 / 7.0
DP15017015	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	1500 / 59.0"	1850 / 72.8"	4.0 / 8.8
DP15017020	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	2000 / 78.7"	2350 / 92.5"	5.3 / 11.6
DP15017030	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	3000 / 118.1"	3350 / 131.8"	8.0 / 17.6
DP15017040	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	4000 / 157.4"	4350 / 171.2"	10.7 / 23.5
DP15017050	150 / 6"	170 / 6.7"	2.0 / 29	112 / 4.4"	5000 / 196.8"	5350 / 210.6"	13.3 / 29.2
DP20022515	200 / 8"	225 / 8.8"	2.0 / 29	150 / 6.0"	1500 / 59.0"	1850 / 72.8"	4.7 / 10.3
DP20022520	200 / 8"	225 / 8.8"	2.0 / 29	150 / 6.0"	2000 / 78.7"	2350 / 92.5"	7.0 / 15.4
DP20022530	200 / 8"	225 / 8.8"	2.0 / 29	150 / 6.0"	3000 / 118.1"	3350 / 131.8"	8.8 / 19.3
DP20022540	200 / 8"	225 / 8.8"	2.0 / 29	150 / 6.0"	4000 / 157.4"	4350 / 171.2"	10.6 / 23.3
DP30015	300 / 12"		1.5 / 22	214 / 8.4"	1500 / 59.0"	1850 / 72.8"	6.5 / 14.3
DP30020	300 / 12"		1.5 / 22	214 / 8.4"	2000 / 78.7"	2350 / 92.5"	8.8 / 19.3
DP30030	300 / 12"		1.5 / 22	214 / 8.4"	3000 / 118.1"	3350 / 131.8"	10.6 / 23.3
DP30040	300 / 12"		1.5 / 22	214 / 8.4"	4000 / 157.4"	4350 / 171.2"	12.4 / 27.2
DP30050	300 / 12"		1.5 / 22	214 / 8.4"	5000 / 196.8"	5350 / 210.6"	14.1 / 31.0
DP40015	400 / 16"		1.5 / 22	290 / 11.4"	1500 / 59.0"	1850 / 72.8"	9.1 / 20.0
DP40020	400 / 16"		1.5 / 22	290 / 11.4"	2000 / 78.7"	2350 / 92.5"	10.8 / 23.7
DP40030	400 / 16"		1.5 / 22	290 / 11.4"	3000 / 118.1"	3350 / 131.8"	14.2 / 31.2